bolta

# Pebble Linen

54”/ TYPE II / 20 oz. **LOW VOC RECYCLED CONTENT**

## PHYSICAL PROPERTIES

| | | |
|---|---|---|
| **Weight** | 20 oz. PLY/620 G/PLM | 13.3 oz. PSY/451 G/PSM |
| **Width** | 54”/137 cm | |
| **Backing** | Osnaburg | |
| **Match** | Reverse, random | |

Custom colors, weights, recycled backing and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

## FIRE SAFETY

- Class “A” Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class “A” NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

## ENVIRONMENT & HEALTH

- **Contains 10% recycled content**
- **Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details**
- **Meets California section 01350 IAQ test requirements for wallcovering**
- **Can contribute to LEED EQ 4.1 for low emitting materials, adhesives, and sealants, if used with low VOC adhesives**
- **Can contribute to LEED MR 5.1 for regional materials**

## ANTIMICROBIAL FEATURES

Bolta® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Bolta® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

## WARRANTY

5 year warranty against manufacturing defects. Additional information is available at www.boltawallcovering.com

© J • JOSEPHSON