

TOWER

Nile Vine Texture

Coordinates with Nile Vine

54"/TYPE II/20 oz. LOW VOC RECYCLED CONTENT

Physical Properties

WEIGHT	20 oz. PLY/620 G/PLM	13.3 oz. PSY/451 G/PSM
WIDTH	54"/137 cm	
BACKING	Osnaburg	
MATCH	Reverse, random	

Custom colors, weights, recycled backing and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

Fire Safety

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

Environment & Health

- Contains 10% recycled content
- Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 for low emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 for regional materials

Antimicrobial Features

TOWER® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All TOWER® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

Warranty

5 year warranty against manufacturing defects. Additional information is available at **www.towerwallcovering.com**

©J•JOSEPHSON