MARCO©

54” Type II • 20 oz.

PHYSICAL PROPERTIES

	U.S. UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY	619 G/PLM
	13.3 oz. PSY	451 G/PSM
Backing	Osnaburg	Osnaburg
Width	54"	137 cm

FEDERAL SPECIFICATIONS

MARCO©, as manufactured by J. Josephson meets or exceeds G.S.A. Federal Specification CCC-W-408D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B.
This wallcovering passes the National Fire Protection Association NFPA286 Corner Burn Test.

FIRE HAZARED CLASSIFICATION RESULTS

- TESTED IN ACCORDANCE WITH ASTM E-84 TUNNEL TEST
- CLASS “A” FIRE RATED
- FLAME SPREAD 15
- SMOKE DEVELOPED 25
- BRITISH BUILDING REG BS/476

Flame Spread	Fire Propagation
Class 1	Class 0

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

All installations must conform to J. Josephson's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES

Vinyl wallcoverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

5 YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

- **STAIN RESISTANT**
- **MILDEW RESISTANT**

ENVIRONMENTAL STATEMENT

We are dedicated to complying with today's environmental issues, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

Use only adhesives and primers as recommended by the manufacturer.

NOTE: The assigned numerical ratings and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

©2004 J.Josephson, Inc. 35 Horizon Boulevard, South Hackensack, NJ 07606

VYCON®
CONTRACT WALLCOVERING