palisade

RECYCLED TYPE II WALLCOVERING



TYPE II High durability, Fed. Spec. CCC-W-408D

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

RECYCLED CONTENT 10% recycled content by weight

BACKING Osnaburg

PATTERN MATCH Reverse hang, random match

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 20, smoke developed 45 (test procedure is comparable to NFPA 255 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 45

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

LOW VOC California Section 01350
Can contribute to LEED® EQ Credit 4.1 for low-emitting materials, adhesives and sealants, if used with low-VOC adhesives

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES
Antimicrobial additives
Cadmium and mercury free
Contains no heavy metals
Does not contain DEHP plasticizers
Free of PBDE's (Brominated Flame Retardants)
Solvent-based inks

CUSTOM CAPABILITIES Custom colors and weights are available

WARRANTY Five year warranty against manufacturing defects

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

© 2015 Wall Source LLC

CROWN
WALLPAPER & FABRICS
Toll free 1.800.268.1300
Sans frais 1.800.361.7881
crownwallpaper.com