LUCERE TEXTURES SPECIFICATIONS

SHEET SIZE / THICKNESS

8" X 96" (2440mm x 1220mm) / 3/8" (9mm)

SURFACE FINISH

Gloss or Matt

CUSTOMISABLE

Colour - minimum order 10 sheets

INDOOR / OUTDOOR

Clear - indoor or outdoor. Coloured - indoor only

WET AREAS

Yes

FABRICATION

Standard wood-working tools

THERMOFORMABLE

Nο

INSTALLATION

An expansion gap of $^{1}/_{16}$ " per 36" (1mm per 1 metre) of product should be allowed for when setting out your sheets. Most glass fittings can be used

REFINISHABLE

Nο

LEAD TIME

8 - 10 weeks.

Express delivery is available subject to a surcharge.

CARE INSTRUCTIONS

In most instances, warm water, mild detergent, and a soft sponge, cloth or chamois will be enough to clean Lucere Textures

ENVIRONMENTAL INFORMATION

Easily recycled. Contact your nearest Crown branch for details

ADDITIONAL COMMENTS

1. Being handmade, slight imperfections in Lucere are deemed acceptable. These slight imperfections may include small bubbles in the interlayer or slight surface texture imperfections. Any imperfection that is not visible 36" (1 meter) away from the panel is deemed within commercial tolerance.

2. Lucere sheets may not be perfectly flat. Due to this, it is always suggested that the sheet be fully framed or mechanically fixed.

3. Lucere can be used as a splashback but NOT behind a stove or cooktop. We recommend a minimum distance of 12" (300mm) from stove or cooktop.