

## QUARTER

Zintra Baffles



Texture: 3 Lustre: 1 Transparency: 2

	1
DESCRIPTION / FEATURES	Zintra Acoustic Baffles are an innovative replacement to a mineral
	fibre lay system. Easy to assemble, easy to install and available
	in a large array of designs, baffles are ideally suited to large noisy
	spaces in educational institutions, shopping centres, restaurants
	and airports. Baffles use at least 1 sheet of Zintra Acoustic Panel
	and an NRC of 0.95.
	Find out more about the Benefits of Zintra and its NRC rating on
	the DOWNLOAD tab.
COMPOSITION	Zintra Acoustic Panel - 100% Polyester
FINISHES AVAILABLE	Zintra Panel - Matt. Available in all 20 Zintra colours.
	Square Tube 25mm x 25mm - Satin Aluminum or Black
STANDARD SIZE	1400mm x 1828mm
	Depth - 110mm



THICKNESS	12mm
SUGGESTED INSTALLATION	Check out the DOWNLOAD tab for a complete Handling and
	Installation guide.
	Be sure to support Baffles during installation to avoid bowing or
	creasing.
	Slide Baffles onto notched Square Tube to position it into place.
	Fix Adjustable Cables to ceiling.
	Adjust cables to complete installation.
LEAD TIME	4-6 weeks
CUSTOMISABLE	Size - Yes
	Zintra Colour - Yes
	Frame Colour - Yes
	Contact Crown Surface Solutions for details.
FIRE	Zintra
INDOOR/OUTDOOR	Indoor only
WET AREAS	No
ENVIRONMENTAL INFORMATION	Easily recycled through standard recycling channels
FIRE RATING	In accordance with ASTM-E84, Zintra™ Acoustic 1/2" Panels
	achieve a Class A Flame Spread - passes CAN ULC S102-10.



ADDITIONAL COMMENTS	NRC - 0.95
	Only available from Zintra Acoustic Panel 12mm.
	Baffle systems include Adjustable Cable Kit and Square Tube.
	See images on website for hardware detail.
	Longer Cables, multi-colour and Digital Print available for an
	additional fee.
SUPPLIED AS	Flat pack.
	Individual Baffles cut to design and size, Square Tube notched
	for easy assembly, Adjustable Cable Kits.
	No screws included.
FABRICATION	Stanley knife if required
CARE INSTRUCTIONS	Remove spills immediately using damp, clean cloth.

Dab Zintra with a clean, soft white cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth. Avoid using wax polishes, solvents or concentrated abrasives.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Dab gently. Repeat using only a clean, water dampened cloth to remove bleach concentration, then pat dry with a lint free cloth. If care instructions don't deliver expected results, cease cleaning method immediately and contact Crown Surface Solutions.