

**TETRIS**  
Zintra Etch



Texture: 1  
Lustre: 1  
Transparency: 1

<p><b>DESCRIPTION / FEATURES</b></p>	<p>Acoustic absorption meets dynamic 3D design with Baresque, the new Zintra Etch. Featuring a range of subtle textures, Zintra Etch will help deliver a cutting-edge but welcoming atmosphere to your next commercial, hospitality or institutional interior.</p> <p>Zintra Etch is available in an extensive range of understated to statement colours and will cultivate calming environs with this cost-effective sound and design solution. Zintra Etch is also easily able to tied back to plain Zintra sheets or talk to us about replicating your Etch pattern in Zintra on Zintra.</p> <p>Zintra Etch Features:</p> <ul style="list-style-type: none"> <li>* Suitable for wall cladding or ceiling</li> <li>* NRC equals at least 0.4</li> <li>* pattern matching with seamless hidden joins (excl VJ Angle and Kaleido)</li> <li>* 2795mm sheet size allows join-free floor-to-ceiling and eas fitout</li> <li>* Designs easily customised to suit your need</li> </ul> <p>Find out more about the Benefits of Zintra and its NRC rating on the DOWNLOAD tab.</p>
--------------------------------------	---

<b>HOW TO SPECIFY</b>	<ol style="list-style-type: none"> <li>1. Design</li> <li>2. Colour</li> <li>3. Zintra Thickness (12mm or 24mm)</li> </ol>
<b>COMPOSITION</b>	Zintra Acoustic Panel - 100% Polyester
<b>FINISHES AVAILABLE</b>	Zintra Panel - Matt. Available in all 20 colours.
<b>SHEET SIZE</b>	2745mm H x 1220mm H  Custom sizes also available
<b>THICKNESS</b>	12mm only
<b>WEIGHT</b>	2.4 kg
<b>INDOOR/OUTDOOR</b>	Indoor only
<b>WET AREAS</b>	No
<b>SUGGESTED INSTALLATION</b>	<p>Check out the DOWNLOAD tab for a complete Handling and Installation guide.</p> <p>Be sure to support the panel during installation to avoid bowing or creasing.</p> <p>Adhere to substrate using contact adhesive, Liquid Nails or Z clips.</p> <p>Panel can also be mechanically fixed using details similar to glass fittings.</p>
<b>LEAD TIME</b>	4-6 weeks.
<b>CUSTOMISABLE</b>	Design - Yes  Colour - Minimums apply. Contact Crown for details.
<b>THERMOFORMABLE</b>	No
<b>FIRE</b>	Zintra
<b>ADDITIONAL COMMENTS</b>	<p>Etch is a 3mm deep V groove. Contact Baresque if alternate depths are required.</p> <p>Not suitable as a free standing product.</p>

<b>SUPPLIED AS</b>	Sheet ready to install
<b>FABRICATION</b>	Stanley knife if required
<b>REFINISHABLE</b>	No
<b>CARE INSTRUCTIONS</b>	Zintra
<b>ENVIRONMENTAL INFORMATION</b>	Easily recycled through standard recycling channels
<b>FIRE RATING</b>	In accordance with ASTM-E84, Zintra™ Acoustic 1/2" Panels achieve a Class A Flame Spread - passes CAN ULC S102-10.

**CARE INSTRUCTIONS**

Remove spills immediately using damp, clean cloth.

Dab Zintra with a clean, soft white cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.

Avoid using wax polishes, solvents or concentrated abrasives.

Repeat using only a clean, water dampened cloth to remove bleach concentration then pat dry with a lint free cloth.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Crown Surface Solutions for assistance.