

PADMESH

Zintra Patterns



Texture: 3 Lustre: 1 Transparency: 1

| DESCRIPTION / FEATURES | The Zintra popular acoustic solution has undergone a style |
|------------------------|---|
| | update to bring you Zintra Patterns. Experience our range of |
| | classic to contemporary screen designs cut out of Zintra. The |
| | perforated panel can be installed as is or matching / contrasting |
| | Zintra backer added to create a unique look for walls or ceilings. |
| | In just the one product you will find style, texture, contrast, depth |
| | and the added benefit of sound absorption to create a |
| | harmonious environment. |
| | * Increased noise absorption |
| | * Easy installation |
| | * Broad range of neutral and bright colour |
| | |
| | |
| | Find out more about the Benefits of Zintra and its NRC rating on |
| | the DOWNLOAD tab. |



| HOW TO SPECIFY | 1. Design |
|------------------------|---|
| | 2. Size |
| | 3. Design Colour |
| | 4. Backing Colour |
| COMPOSITION | Zintra Acoustic Panel - 100% Polyester |
| FINISHES AVAILABLE | Zintra Panel - Matt. Available in all 20 Zintra colours. |
| SHEET SIZE | 610mm x 610mm |
| | 1220mm x 610mm |
| | 2745mm x 1220mm |
| | |
| | Pattern only - 12mm |
| | Pattern later on backer - 24mm |
| INDOOR/OUTDOOR | Indoor only |
| WET AREAS | No |
| SUGGESTED INSTALLATION | Check out the DOWNLOAD tab for a complete Handling and |
| | Installation guide. |
| | Be sure to support the panel during installation to avoid bowing or |
| | creasing. |
| | Adhere to substrate using contact adhesive, Liquid Nails or Z |
| | clips. |
| | Panel can also be mechanically fixed using details similar to |
| | glass fittings. |



| LEAD TIME | 4-6 weeks. |
|---------------------------|---|
| CUSTOMISABLE | Design - Yes |
| | Colour - Yes |
| | Contact Crown Surface Solutions for details |
| THERMOFORMABLE | No |
| FIRE | Zintra |
| ADDITIONAL COMMENTS | Not suitable as a free standing product. |
| | NRC - 0.45 - 0.95 |
| FABRICATION | Stanley knife if required |
| REFINISHABLE | No |
| CARE INSTRUCTIONS | Zintra |
| ENVIRONMENTAL INFORMATION | Easily recycled through standard recycling channels |
| FIRE RATING | In accordance with ASTM-E84, Zintra™ Acoustic 1/2" Panels |
| | achieve a Class A Flame Spread - passes CAN ULC S102-10. |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |



| SUPPLIED AS | Sheet ready to install |
|-------------------|--|
| CARE INSTRUCTIONS | Remove spills immediately using damp, clean cloth. |
| | Dab Zintra with a clean, soft white cloth dampened with a mild |
| | solution of liquid detergent and warm water. Repeat using only |
| | clean water, then pat dry with a lint free cloth. |
| | Avoid using wax polishes, solvents or concentrated abrasives. |
| | For more difficult stains, dampen a soft white cloth with a solution |
| | of household bleach (10% bleach / 90% water). Dab gently. |
| | Repeat using only a clean, water dampened cloth to remove |

bleach concentration, then pat dry with a lint free cloth.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Crown Surface Solutions for assistance.